









## RocketDish: 5GHz AirMax 2x2 MIMO PtP Dish Antenna Series

RocketDish5G-30		Return Loss	E-Plane, 5500MHz	E-Plane Specs	H-Plane, 5500MHz	H-Plane Specs
	Antenna Characteristics					
	Frequency Range	4.9-5.90 GHz				
	Gain	28.0-30.25 dBi				
	Polarization	Dual Linear				
	Cross-pol Isolation	35dB min				
	Max VSWR	1.4:1				
	Hpol Beamwidth(3dB)	5 deg.				
	Vpol Beamwidth(6dB)	5 deg.				
	F/B Ratio	-34dB				
	ETSI Specification	EN 302 326 DN2				
	Dimensions	648mm diameter				
	Weight	9.8 kg				
	Wind Survivability	120 mph				
Windloading	113lb@100mph					

RocketDish5G-34		Return Loss	E-Plane, 5500MHz	E-Plane Specs	H-Plane, 5500MHz	H-Plane Specs
	Antenna Characteristics					
	Frequency Range	4.9-5.90 GHz				
	Gain	32.1-34.2 dBi				
	Polarization	Dual Linear				
	Cross-pol Isolation	35dB min				
	Max VSWR	1.4:1				
	Hpol Beamwidth(3dB)	3 deg.				
	Vpol Beamwidth(6dB)	3 deg.				
	F/B Ratio	-42dB				
	ETSI Specification	EN 302 326 DN2				
	Dimensions	972mm diameter				
	Weight	13.5 kg				
	Wind Survivability	125 mph				
Windloading	256lb@100mph					

**rocket M5**

Instantly pair with Rocket M5 to create powerful 2x2 MIMO PtP Bridging applications. Full mating brackets and weatherproof RF jumpers included.

